

SUPER-SPRAYFAST™

UNIVERSAL

ADHESIVE APPLICATING SYSTEM FOR WATER-BASED ADHESIVES

ITEM # 5151

The revamped Universal version of our Super Sprayfast Adhesive Applicator (SSFU) machine makes it possible to use the same applicator on either a 5 gallon bucket or 55 gallon drum. In addition, it now also includes a new flush kit for easy clean up and maintenance (more information on back). The SSFU features an acetal/teflon diaphragm pump **circulating system** and **surge tank** to provide quick, easy and even spray, with minimal overspray.

ITEM# 5151

(Adhesive not included.)



Reliable

The acetal and teflon air operated diaphragm pump coupled with the circulating system keeps the adhesive fresh. The built in surge tank helps maintain an even spray. The spray gun is constructed of aluminum and stainless steel to resist corrosion.

Safe

The SSFU has been designed for use with Duro Dyne's WIT, WSA and SSG water-based adhesives. These adhesives are nonflammable and contain zero solvents. No venting is required.

Ease of Operation

Place the pump (factory mounted to the cover) on top of the adhesive container. Attach the air-line to the Super Sprayfast Universal pump. The pump is self-priming and charges the spray gun quickly. A 15-foot hose gives the operator plenty of freedom of movement.

Versatile


The Super Sprayfast Universal is designed for use with 5 gallon pails or 55 gallon drums of water-based adhesive.

Flush Kit Assembly

For optimum performance, it is recommended that you flush out your Super Sprayfast Universal Machine (SSFU) weekly. The new flush kit of the SSFU model makes this clean up and maintenance procedure easier than ever before. Simply close the glue valve, open the water valve and set your water hose into a 5 gallon pail of water. Then, spray out any remaining glue in your hose. The pump will flush out the hoses for the next use.

MACHINERY DIVISION
© 2015 Duro Dyne Corporation
Printed in USA 12/2015
BC039406

**DURO
DYNE®**



Flush Kit includes
Pick Up Tube for 5 gallon
pail and 55 gallon drum

Specifications

Air Requirements
Pump: 80 PSI 2 CFM
Atomization: 15-100 PSI
15-24 CFM

Ordering Info

Item#	Description
5151	Super Sprayfast Universal for use with 5 gallon pail and 55 gallon drum of water-based adhesive

The Super Sprayfast Universal is specifically designed for use with Duro Dyne Water-Based Adhesives:

WIT, WITLV-AS, SSG, WSA



Duro Dyne East Division, Bay Shore, NY
Duro Dyne Midwest Division, Fairfield, OH
Duro Dyne West Division, Fontana, CA
Duro Dyne Canada, Lachine, Quebec, Canada

www.durodyne.com

631-249-9000 Fax: 631-249-8346
513-870-6000 Fax: 513-870-6005
562-926-1774 Fax: 562-926-5778
514-422-9760 Fax: 514-636-0328

E-mail: durodyne@durodyne.com