

SUBMITTAL RECORD \_\_\_\_\_  
 JOB \_\_\_\_\_  
 LOCATION \_\_\_\_\_  
 SUBMITTED TO \_\_\_\_\_  
 SUBMITTAL PREPARED BY \_\_\_\_\_  
 APPROVED BY \_\_\_\_\_  
 DATE \_\_\_\_\_



# Submittal Form Duro-Gum™

## DESCRIPTION

Duro-Gum is a gray, permanently soft, non-toxic compound which will adhere to most clean dry surfaces. It has countless applications in the refrigeration, heating and cooling, plumbing, and metal fabrication fields. It will seal around electrical boxes, flashings, and service mast entries. Duro-Gum can be shaped by hand to any form and reused if necessary. It is an excellent general purpose sealant.



**FLAME SPREAD:** 5  
**SMOKE DEVELOPED:** 15

## FEATURES

- Meets UL 723
- FDA Approved
- U.S.D.A. Acceptable
- Dielectric Strength: Approx. 200 volts per mil (ASTM D149-64) or 10 KV
- Chemical Resistance: Excellent resistance to water, alcohols, mild acids and bases
- Vehicle Bleedout: None
- Non-Corrosive: Will not corrode Metals
- Non-Irritant: No irritation to eyes or skin as listed in CFR, Title 16, "Appraisal of the safety of chemicals in food, drugs, and cosmetics"
- Paintable

## TYPICAL PROPERTIES

**Color:** Gray  
**Base:** Non-drying synthetic polymers and oils  
**Temp. usage range:** 25°F to +120° F  
**Temp. tolerance range:** -30°F to +175° F  
**Specific Gravity:** 1.65 to 1.7  
**Cone penetration:** Load of 300 gm..5 sec. @ 25°F;  
 100 -115 mm/10

Item #	Code	Description
21048	BTLG1	Duro-Gum

Duro Dyne East Division, Bay Shore, NY	631-249-9000	Fax: 631-249-8346
Duro Dyne Midwest Division, Hamilton, OH	513-870-6000	Fax: 513-870-6005
Duro Dyne West Division, Fontana, CA	562-926-1774	Fax: 562-926-5778
Duro Dyne Canada, Lachine, Quebec, Canada	514-422-9760	Fax: 514-636-0328
www.durodyne.com E-mail: durodyne@durodyne.com		

