



## Quad Cleat® Plus

The Heavy Duty Quad Cleat Plus is designed specifically for high pressure, heavy duty transverse duct.

Creating a secure seal between sections of ductwork is important to minimizing system leakage. Sections of duct utilizing four bolt flange systems must sit securely against the gasket installed between mating ductwork. While corners of duct are bolted together, the flange between the bolts utilize cleats to apply pressure to the flanges, encapsulated gasket and eliminate deflection.

Both Quad Cleats incorporate embossed "darts" which help the cleat lock firmly onto the flange. It is a universal fastener for use with most commercial size flanges. If you use more than one brand of flange, this eliminates the need to stock more than one cleat.

### FEATURES

- Both are compatible with Dyn-O-Mate® J, Ductmate™ 35, CL Ward™ J, Ward Industries™ J, Hardcast™ flanges, TDC, TDF and TDX Connections
- QXCLT20-125 is manufactured from 20 ga galvanized steel
- DOMQCLT125 & HDQC-PLUS125 are manufactured from 22 ga galvanized steel
- Other gauges and materials available upon request.

### Ordering Information

Item #	Code	Description	Quantity	Weight (lbs.)
13096	DOMQCLT125	6in. Quad Cleat 22ga	125' - 250 6" pcs/box	TBD
13100	QXCLT20-125	6in. Quad Cleat - 20ga	125' - 250 6" pcs/box	TBD
13175	HDQC-PLUS125	6in. Heavy Duty Quad Cleat Plus - 22ga	125' - 250 6" pcs/box	TBD

Duro Dyne Corporate Headquarters, Bay Shore, NY  
631-249-9000 • Fax: 631-249-8346  
Duro Dyne Midwest • Duro Dyne West • Duro Dyne Canada  
www.durodyne.com • E-mail: durodyne@durodyne.com



© 2020 Duro Dyne Corp.  
Printed in USA 3/2020  
BF013415