



HANGING STRAP

Duro Dyne provides Hanging Strap fabrics that are waterproof, grease, oil & acid resistant, and have low smoke & flame development.

FEATURES

- Lightweight
- Low cost
- High Strength Design
- Easy Installation
- Helps Eliminate Rattling
- Supports Flexible Duct Without Damaging
- Outer Jacket
- Waterproof & Airtight

DESIGNED FOR HANGING

- Flexible Duct
- PVC Vent Duct
- Duct Board Systems
- Many Lighter Weight Steel
- Duct Applications



Fasten Strap To Beams

TECHNICAL INFORMATION	VINYL DURO STRAP
FLAME SPREAD & SMOKE DEVELOPMENT:	NFPA Class A* UBC Class 1*
TENSILE STRENGTH:	Warp-70 lbs./In. Fill-70 lbs./In
HEAT RESISTANCE:	200° F
TEAR STRENGTH:	Warp- 8 lbs./In. Fill-11 lbs./In
FABRIC:	Black vinyl coated polyester fill
TOTAL FABRIC THICKNESS:	.022" Approx.
QUANTITY PER CARTON:	10 rolls (Conveniently packaged in a dispenser box with cutting blade)
ADDITIONAL INFO:	*Product Meets NFPA Class A and UBC Class 1 characteristics of flame spread less than 25 and smoke development less than 50 when utilizing test method ASTM E-84.

Ordering Information

Item #	Code	Description	Quantity
10190	VDS200	Vinyl Duro Strap 1-1/2" x 200'	200 ft. Roll



Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346
 Duro Dyne Midwest Division, Fairfield, OH 513-870-6000 Fax: 513-870-6005
 Duro Dyne West Division, Fontana, CA 562-926-1774 Fax: 562-926-5778
 Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328
 www.durodynecanada.ca E-mail: durodynecanada@durodyne.com



© Duro Dyne Corp.
 Duro Dyne Canada
 JB 0317