



# AIR REGULATION

## Extreme Temperature Dyn-O-Ties®



Extreme Temperature Dyn-O-Ties from Duro Dyne provide secure joints when connecting flexible duct. Designed for application in extreme climates with temperatures from -40° F to 221° F. These special feature Dyn-O-Ties are a high visibility yellow so they can be easily inspected on any job site.

- High Impact Nylon
- High Visibility Yellow
- Operating Temperature: -40° F to 221° F
- Minimum Installation Temperature: -4° F
- UV Resistant
- Designed to meet UL181



Installs easily with  
the Duro Dyne  
Dyn-O-Tie Gun  
DIT3 Part #7343



Proudly Made  
in the USA

### Ordering Information

Item #	Code	Description	Color	Length	Max. Dia.	Quantity
6317	AWT36USA	High Visibility Extreme Temp. Dyn-O-Tie - USA Made	Yellow	36"	11"	50/bag - 10 bags of 50/box

Duro Dyne East Division, Bay Shore, NY	631-249-9000	Fax: 631-249-8346
Duro Dyne Midwest Division, Hamilton, OH	513-870-6000	Fax: 513-870-6005
Duro Dyne West Division, Fontana, CA	562-926-1774	Fax: 562-926-5778
Duro Dyne Canada, Lachine, Quebec, Canada	514-422-9760	Fax: 514-636-0328
www.durodyne.com E-mail: durodyne@durodyne.com		



© Duro Dyne Corp.  
Printed in USA 8/6/18  
BC008412