SUBMITTAL RECORD JOB ______ LOCATION______ SUBMITTED TO______ SUBMITTAL PREPARED BY__ APPROVED BY_____ DATE



Submittal Form VR2 VANE RAIL

DESCRIPTION

Air traveling through a duct is slowed up when it encounters a right angle turn of an elbow or a T shaped fitting.. This "slow-up" can disrupt the air flow and is detrimental to the efficiency of the duct system. Therefore air turning vane assemblies are used to guide air evenly around such turns. These assemblies are comprised of turning vanes, which are often fabricated by the contractor, and rails which are supplied by the manufacturer with embossing and pre-stamped slots to position the turning vanes.




SUGGESTED SPECIFICATIONS

Right angled fittings shall incorporate air turning vane assemblies as determined by the design engineer. Assemblies shall be comprised of turning vanes mounted to SMACNA Type 2 Runner called vane rail and coded _______as manufactured by

Duro Dyne Corporation.

See Notes on fig. 4.3 & 4.4 in SMACNA Third Edition 2005.



ITEM	CODE	DESCRIPTION	QUANTITY
4002	VR2	Galvanized Steel Vane Rail	100 ft. Continuous Coil
4003	JVR2	Galvanized Steel Junior Vane Rail	Two 100 ft. Continuous Coils
4007	VR2SS	300 Series Stainless Steel Vane Rail	100 ft. Continuous Coil
4008	VR2AL	Aluminum Vane Rail	100 ft. Continuous Coil

Duro Dyne East Division, Bay Shore, NY631-249-9000Fax: 631-249-8346Duro Dyne Midwest Division, Hamilton, OH513-870-6000Fax: 513-870-6005Duro Dyne West Division, Fontana CA562-926-1774Fax: 562-926-5778Duro Dyne Canada, Lachine, Quebec, Canada514-422-9760Fax: 514-636-0328www.durodyne.comE-mail: durodyne@durodyne.com

