



## NEOPRENE FLEXIBLE DUCT CONNECTOR NOW AVAILABLE IN 700 FOOT ROLLS FOR METAL-FAB, ECONO-O-FAB AND TDC/TDF.

- The Industry Standard for HVAC Systems
- For High Pressure and High Velocity Systems
- Strong – Airtight – Waterproof – Mildew Resistant
- Resists many acids, alkalis, grease, oil and gasoline
- For systems exposed to toxic fumes and polluted atmosphere

**Metal-Fab** meets the requirements of most commercial and industrial applications, allowing for absorption of normal equipment-created vibration and preventing it from being transmitted through the duct system.

Grade: Commercial

Dimensions: 3" metal 3" fabric 3" metal

Gauge: 24

Seam: Grip-Loc



Item No.	Code	Description	Feet/Roll	Weight/Roll	Skid Qty
10316	<b>MFN-700 333</b>	3x3x3 Neoprene Connector	700	539 Lbs	5 Rolls

**Econ-O-Fab** is for light commercial and residential applications.

Dimensions: 3" metal 3" fabric 3" metal

Gauge: 28

Seam: Grip-Loc

Item No.	Code	Description	Feet/Roll	Weight/Roll	Skid Qty
10317	<b>EFN-700 333</b>	3x3x3 Neoprene Connector	700	350 Lbs	5 Rolls

**TDC/TDF** Connector is specially manufactured for use by shops producing duct with Lockformer TDC or Engel TDF flange-forming machines.

Dimensions: 4" metal 4" fabric 4" metal

Gauge: 24

Seam: Grip-Loc

Item No.	Code	Description	Feet/Roll	Weight/Roll	Skid Qty
10315	<b>MFN-700 444</b>	4x4x4 Neoprene Connector	700	672 Lbs	4 Rolls