



#### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 21, 2019

### 1 Identification

· Product identifier

· Trade name: WIT5LVAS WIT50LVAS AIRLESS SPRAYABLE DUCT LINE ADHESIVE

· Product code: 5106, 5107

· Recommended use and restriction on use

· Recommended use: Adhesives

· Restrictions on use: For professional use only.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier: DURO DYNE CANADA 2365 46E AVENUE LACHINE, QUEBEC H8T 3C9

800-899-3876

**Emergency telephone number:** 

ChemTel Inc.

(800)255-3924 (North America) 1 (813)248-0585 (International) (801)

#### 2 Hazard(s) identification

· Classification of the substance or mixture

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Warning · Hazard statements:

H317 May cause an allergic skin reaction.

· Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse. P363

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

(Cont'd. on page 2)





#### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 21, 2019

#### Trade name: WIT-LVAS AIRLESS SPRAYABLE DUCT LINE ADHESIVE

(Cont'd. of page 1)

· Chemical characterization: Mixtures

| · Components: |  |        |  |  |
|---------------|--|--------|--|--|
| 471-34-1      | Calcium carbonate  | <20%   |  |  |
| 57-55-6       | Propylene glycol   | <3%    |  |  |
| 107-21-1      | Ethylene glycol STOT RE 2, H373 Acute Tox. 4, H302   | <3%    |  |  |
| 127087-87-0   | 4-Nonylphenol, branched, ethoxylated  Acute Tox. 4, H302; Eye Irrit. 2A, H319  | <1%    |  |  |
| 13463-67-7    | Titanium dioxide   | <1%    |  |  |
| 4719-04-4     | 2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol Acute Tox. 2, H330 STOT RE 1, H372 Acute Tox. 4, H302; Eye Irrit. 2A, H319; Skin Sens. 1, H317                    | <1%    |  |  |
| 55965-84-9    | 2-Methyl-1,2-thiazol-3(2H)-one - 5-chloro-2-methyl-1,2-thiazol-3(2H)-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 | <0.05% |  |  |

#### Additional information:

Non-classification as a carcinogen is based on non-respirable form of product.

Petroluem-based ingredients pass the IP-346 assay for polycyclic aromatic compounds.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

For the wording of the listed Hazard Statements, refer to section 16.

#### 4 First-aid measures

- Description of first aid measures
- · After inhalation:

Respiration of particulates is unlikely during normal usage.

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately remove any clothing soiled by the product.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Allergic reactions

Slight irritant effect on eyes.

Slight irritant effect on skin and mucous membranes.

Nausea in case of ingestion.

Gastric or intestinal disorders when ingested.

Indication of any immediate medical attention and special treatment needed:

Contains 2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol, 2-Methyl-1,2-thiazol-3(2H)-one - 5-chloro-

(Cont'd. on page 3)





#### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 21, 2019

#### Trade name: WIT-LVAS AIRLESS SPRAYABLE DUCT LINE ADHESIVE

(Cont'd. of page 2)

2-methyl-1,2-thiazol-3(2H)-one. May produce an allergic reaction.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

# 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

The product is not flammable.

Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

- · Environmental precautions Avoid release to the environment.
- · Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- ·Handling
- · Precautions for safe handling:

Keep out of reach of children.

Use only in well ventilated areas.

Use personal protective equipment as required.

- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Do not allow product to freeze.

· Information about storage in one common storage facility:

Store away from foodstuffs.

(Cont'd. on page 4)





# according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 21, 2019

### Trade name: WIT-LVAS AIRLESS SPRAYABLE DUCT LINE ADHESIVE

(Cont'd. of page 3)

Do not store together with oxidizing and acidic materials.

· Specific end use(s) No relevant information available.

# 8 Exposure controls/personal protection

| · Control parameters   |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| Components with limit values that require monitoring at the workplace:   |  |  |  |  |  |  |
| 471-34-1 Calcium carbonate   |  |  |  |  |  |  |
| PEL (USA)  | Long-term value: 15* 5** mg/m³   |  |  |  |  |  |
|  | *total dust **respirable fraction  |  |  |  |  |  |
| REL (USA)  | Long-term value: 10* 5** mg/m³ *total dust **respirable fraction   |  |  |  |  |  |
| TLV (USA)  | TLV withdrawn  |  |  |  |  |  |
| 57-55-6 Propyle  | ene glycol   |  |  |  |  |  |
| WEEL (USA)   | Long-term value: 10 mg/m³  |  |  |  |  |  |
| EV (Canada)  | Long-term value: 155* 10** mg/m³, 50* ppm *vapour and aerosol;**aerosol only                                 |  |  |  |  |  |
| 107-21-1 Ethyle  | 107-21-1 Ethylene glycol   |  |  |  |  |  |
| TLV (USA)  | Short-term value: 10** mg/m³, 50* ppm Long-term value: 25* ppm *vapor fraction:**inh. fraction, aerosol only |  |  |  |  |  |
| WEEL (USA)   | I (2)  |  |  |  |  |  |
| EL (Canada)  Short-term value: 20** mg/m³ Long-term value: 10** mg/m³ Ceiling limit value: 100* mg/m³, 50*** ppm  *Aerosol; **Particulate; ***Vapour |  |  |  |  |  |  |
| EV (Canada)  | Ceiling limit value: 100 mg/m³   |  |  |  |  |  |
| LMPE (Mexico)  | Ceiling limit value: 100* mg/m³ A4, *solo aerosol  |  |  |  |  |  |
| 13463-67-7 Tita  | nium dioxide   |  |  |  |  |  |
| PEL (USA)  | Long-term value: 15* mg/m³ *total dust   |  |  |  |  |  |
| REL (USA)  | See Pocket Guide App. A  |  |  |  |  |  |
| TLV (USA)  | Long-term value: 10 mg/m³  |  |  |  |  |  |
| EL (Canada)  | Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B                                    |  |  |  |  |  |
| EV (Canada)  | Long-term value: 10 mg/m³ total dust   |  |  |  |  |  |
| LMPE (Mexico)  | Long-term value: 10 mg/m³<br>A4  |  |  |  |  |  |

#### • Exposure controls

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

(Cont'd. on page 5)





### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 21, 2019

#### Trade name: WIT-LVAS AIRLESS SPRAYABLE DUCT LINE ADHESIVE

(Cont'd. of page 4)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Engineering controls: No relevant information available.
- Breathing equipment:

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection:

Protective work clothing

Protection may be required for spills.

· Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

# 9 Physical and chemical properties Information on basic physical and chemical properties

· Appearance: Form: Liquid Color: White · Odor: Characteristic · Odor threshold: Not determined. · pH-value: 7.5-9.0 Melting point/Melting range: ~0 °C (~32 °F) · Boiling point/Boiling range: ~100 °C (~212 °F) · Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. · Auto-ignition temperature: Not determined. Decomposition temperature: Not determined. Danger of explosion: Product does not present an explosion hazard. · Explosion limits (Cont'd. on page 6)





#### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 21, 2019

#### Trade name: WIT-LVAS AIRLESS SPRAYABLE DUCT LINE ADHESIVE

(Cont'd. of page 5) Lower: Not determined. Upper: Not determined. Oxidizing properties: Non-oxidizing. · Vapor pressure: Not determined. · Density: Relative density: 1.3 Vapor density: Not determined. **Evaporation rate:** Not determined. · Solubility in / Miscibility with Water: Fully miscible. · Partition coefficient (n-octanol/water): Not determined. · Viscosity **Dynamic:** >2000 cP Kinematic: Not determined. Other information No relevant information available.

# 10 Stability and reactivity

- · Reactivity: No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with strong acids and oxidizing agents.

- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers, strong bases, strong acids
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Toxic metal oxide smoke

# 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

| · LD/LC50 values that are relevant for classification:             |                   |  |                     |  |  |  |
|--|-------------------|--|---------------------|--|--|--|
| 107-21-1 Ethylene glycol   |                   |  |                     |  |  |  |
| Dermal   | LD50              | 9530 mg/kg (rabbit)                    |                     |  |  |  |
| 4719-04-4 2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol |                   |  |                     |  |  |  |
| Oral   | LD50              | 750-1250 mg/kg (rat) (Estimated Range) |                     |  |  |  |
| Inhalative   | LC50/4h (dynamic) | 0.37 mg/l (rat)                        |                     |  |  |  |
|  |                   |  | (Cont'd. on page 7) |  |  |  |





### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 21, 2019

#### Trade name: WIT-LVAS AIRLESS SPRAYABLE DUCT LINE ADHESIVE

(Cont'd. of page 6)

- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization:

Contains 2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol, 2-Methyl-1,2-thiazol-3(2H)-one - 5-chloro-2-methyl-1,2-thiazol-3(2H)-one. May produce an allergic reaction.

#### · IARC (International Agency for Research on Cancer):

13463-67-7 Titanium dioxide

2B

# · NTP (National Toxicology Program):

None of the ingredients are listed.

### · OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

#### · Probable route(s) of exposure:

Ingestion.

Inhalation.

Eve contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity:

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

- Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes: Avoid release to the environment.
- · Other adverse effects No relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

(Cont'd. on page 8)





#### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 21, 2019

# Trade name: WIT-LVAS AIRLESS SPRAYABLE DUCT LINE ADHESIVE

(Cont'd. of page 7)

**Uncleaned packagings** 

· Recommendation: Disposal must be made according to official regulations.

| 14 Transport information  |                       |  |  |
|---|-----------------------|--|--|
| · UN-Number<br>· DOT, ADR/RID/ADN, IMDG, IATA                     | Not regulated.        |  |  |
| · UN proper shipping name<br>· DOT, ADR/RID/ADN, IMDG, IATA       | Not regulated.        |  |  |
| ·Transport hazard class(es)                                       |                       |  |  |
| · DOT, ADR/RID/ADN, IMDG, IATA<br>· Class                         | Not regulated.        |  |  |
| · Packing group<br>· DOT, ADR/RID/ADN, IMDG, IATA                 | Not regulated.        |  |  |
| · Environmental hazards<br>· Marine pollutant:                    | No                    |  |  |
| · Special precautions for user                                    | Not applicable.       |  |  |
| Transport in bulk according to Annex MARPOL73/78 and the IBC Code | II of Not applicable. |  |  |

# 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

107-21-1 Ethylene glycol

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7 Titanium dioxide

(Cont'd. on page 9)





#### according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 21, 2019

#### Trade name: WIT-LVAS AIRLESS SPRAYABLE DUCT LINE ADHESIVE

(Cont'd. of page 8) · Chemicals known to cause developmental toxicity for females: None of the ingredients are listed. Chemicals known to cause developmental toxicity for males: None of the ingredients are listed. Chemicals known to cause developmental toxicity: 107-21-1 Ethylene glycol **EPA (Environmental Protection Agency):** None of the ingredients are listed. · IARC (International Agency for Research on Cancer): 13463-67-7 Titanium dioxide 2B

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

Canadian Domestic Substances List (DSL):

DOT: US Department of Transportation

IATA: International Air Transport Association

All ingredients are listed or exempt.

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

#### Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers