



PVC Quad Cleat[™]

Creating a secure seal between sections of ductwork is important to minimizing system leakage. Sections of duct utilizing four bolt flange systems must seat securely against the gasket installed between mating ductwork. While corners of duct are bolted together, the flange between the bolts utilize cleat to apply pressure to the flanges, encapsulated gasket and eliminate deflection.

The PVC Quad Cleat is a universal fastener for use with most commercial size flanges. If you use more than one brand of flange, this eliminates the need to stock more than one cleat. It is designed for Breakaway Connections.

FEATURES

- Compatible with Dyn-O-Mate[™] J, Ductmate[™] 35, CL Ward[™] J, Ward Industries[™] J, Hardcast[™] flanges, TDC, TDF and TDX Connections - and most competitive Flanges on the market.
- Cleat is Duro Dyne yellow in color
- UL 94 -VO
- PVC Material is compliant to ASTM D1784

Ordering Information

Item #	Code	Description	Quantity	Weight (lbs.)
13108	PQCLT	PVC Quad Cleat - 6"	250' - 500 6" pcs/box	19

Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346
 Duro Dyne Midwest Division, Hamilton, OH 513-870-6000 Fax: 513-870-6005
 Duro Dyne West Division, Fontana, CA 562-926-1774 Fax: 562-926-5778
 Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328
 www.durodyne.com E-mail: durodyne@durodyne.com