



## Snap Hook Cables



### FEATURES

- Aviation grade galvanized wire rope
- Tested to verify breaking strengths
- Utilizes 7x7 construction

The Dyna-Tite suspension system utilizes cable locks and wire rope to secure ductwork and equipment. This method has been shown to reduce installation time and improve safety at the job site when compared to traditional hanging methods such as threaded rod, perforated strap, and band iron. Snap hook cables offer easy attachment points and are ideal for applications that require constant inspection or maintenance that may require you to remove the load from the ceiling.

Item #	Code	Description	For Use w/ Cable Lock	Safe Working Load*	Packaged
30217	SH05WC3	Snap Hook Swaged 5 ft WC3-CL12 Cable	CL12-WC3	25-150 lbs. (12-68 kg)	10/bag-5bg/bx
30218	SH10WC3	Snap Hook Swaged 10 ft WC3-CL12 Cable	CL12-WC3	25-150 lbs. (12-68 kg)	10/bag-5bg/bx
30219	SH15WC3	Snap Hook Swaged 15 ft WC3-CL12 Cable	CL12-WC3	25-150 lbs. (12-68 kg)	10/bag-5bg/bx
30223	SH25WC3	Snap Hook Swaged 25 ft WC3-CL12 Cable	CL12-WC3	25-150 lbs. (12-68 kg)	5/bag-5bg/bx

\*Safe Working Loads are based on a 5:1 Safety Factor

To ensure maximum safety, use only looped wire rope supplied by Duro Dyne with cable lock applications.

Duro Dyne East Division, Bay Shore, NY	631-249-9000	Fax: 631-249-8346
Duro Dyne Midwest Division, Hamilton, OH	513-870-6000	Fax: 513-870-6005
Duro Dyne West Division, Fontana, CA	562-926-1774	Fax: 562-926-5778
Duro Dyne Canada, Lachine, Quebec, Canada	514-422-9760	Fax: 514-636-0328
www.durodyne.com E-mail: durodyne@durodyne.com		

